

Data sheet

Commercial Art.No.: 78.913.0253.0

Modular insert FLE STP 2 2.5

Modular connector system male insert with two connections, with brass valve, Ø 2,5 mm



| | |
|--------------------|---------------|
| Commercial Art.No. | 78.913.0253.0 |
| EAN | 4015573782631 |
| Order Unit | 5 |

Technical data

General

| | |
|--|------------|
| Model | Pin insert |
| Inflammability class of insulation material acc. with UL94 | V0 |
| Color | black |
| Modular version | yes |
| Operating temperature range min. | -40 °C |
| Operating temperature range max. | 100 °C |

Connection Data

| | |
|--|-----------|
| Connection type | Pneumatic |
| Number of poles | 2 |
| Plus switching contacts | 0 |
| Number of pole for rated current 2 | 0 |
| Number of pole for rated current 3 | 0 |
| Total number of poles (without ground contact) | 2 |
| With wire protection | No |
| Protective contact | No |

Model

| | |
|--------------|----|
| With housing | No |
|--------------|----|

Contacts

| | |
|------------------|-------|
| Contact material | Other |
| Surface | Other |

Classification

| | |
|------------|----------|
| ECLASS 11 | |
| ECLASS 8.1 | 27440205 |
| ETIM 7.0 | EC000438 |
| ETIM 6.0 | EC000438 |
| ETIM 5.0 | EC000438 |
| ETIM 4.0 | EC000438 |
| ETIM 3.0 | EC000438 |

Product compliance

| | |
|------------------------------|-----------|
| ROHS conformity status | Compliant |
| REACH-SVHC conformity status | Compliant |

Zeichnungsnummer
78.913.0253.010W
Moduleinsatz

Moduleinsatz
78.913.0253.0

15.11.2007
Hollet Florian
M 1:1

