



公差等级/General tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	3	6	10	18	30	50	80	120	180	250	315	400	500	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.50	±2.20	±2.50	±2.50	±Z	±Z

UL 标准/UL Standard:		B	C	D
额定电压/Rated Voltage(V)	Current(A)	300/15	/	300/10
EC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree				
额定电压/电压/Rated Voltage(V)/Current(A)	III/3	III/2	II/2	/
额定电压/电流/Rated Voltage(V)/Current(A)	/	320/20	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/	/
间距/Pitch(mm)/线数范围/Noes	5.08/N=02~24P			
使用温度范围/Operating Temperature(°C)	-40~+105			
符合RoHS环保要求/Conform to RoHS	Yes			
标准颜色编号/Standard color number:	/			
PANTONE / RAL	/			

PCB LAYOUT

ITEM	NAME OF PART	MATERIAL	NOTES
4	Screw Cap	Copper alloy	
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: L:GL 2020.06.22

CHKD: MaoJ 2020.06.22

DRAFT: WangY2 2020.06.22

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE:A4	SCALE: 2:1	SHEET
1							1/1

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

ZEDGAM-5.08-XXP-14-00A(H)

DRAWING NO.: ZEDGAM-5.08-C01