



未注尺寸公差

Pitch Range in mm	Over	In	"Dim.b" Dimension Range in mm	Over	Nominal Dimension Range in mm	Over	Over	Over	Over	Over	Over	Over	Over
TO	6	TO	TO	30	TO	60	TO	100	TO	150			
6	TO	24	TO	60	TO	100	TO	150					
±0.075	±0.15	±0.20	±0.20	±0.35	±0.50	±0.75	±1.00	±0.075	±0.15				

订货信息 Order Info	
订货号 PART NUMBER	颜色 COLOR
225942	灰色 Gray

IEC 额定数据/IEC Rated data

接线范围/Wire range	0.2-2.5mm ²
单股导线/Solid	0.2-2.5mm ²
软导线/Stranded	0.2-2.5mm ²
带端头软导线/Stranded with ferrules without plastic sleeve	0.2-1.5mm ²
带预绝缘端头软导线/Stranded with ferrules with plastic sleeve	0.2-1.5mm ²
剥线长度/Strip length	8-9mm
额定电压/Rated voltage	250V
额定电流/Rated current	0.5A
额定脉冲耐受电压/Rated surge voltage	8KV
污染等级/Pollution degree	3
过电压类别/Surge voltage category	III
UL 额定数据/UL Rated data	B C D
额定电流/Rated current	0.5A 0.5A
额定电压/Rated voltage	250V 250V
接线范围/Wire range	24-12AWG

其他信息/Other information

塑件/Housing	PA66
触点材料/Contact	铜合金/Copper alloy
镀层/Coating	锡/Tin
阻燃等级/Flame retardant rating	V0
使用环境温度/Usage ambient temperature	-25°C - +70°C
储存及运输环境温度/Storage ambient temperature	-40°C - +85°C
导轨尺寸/rails Size	SP35X7.5/SP35X15

认证/Approval



Rev. 01	Name
225942	225942 2X2 通道正面向中 标带 二极管 B 型接线端子
mm	225942 2X2 conductor through terminal blocks with of front-entry and diode (type B)