

**Verpackungsmöglichkeiten:**

Ampopack: 5.000 St. in der Schachtel


**Packing opinions:**

Ammo pack: 5.000 pcs. per inner box



**Bemessungswerte / Ratings**

Art.-No.	Strom Current	Spannung Voltage	Ausschaltvermögen Breaking capacity	Spannungsfall Voltage drop max [mV]	Schmelzintegral Melting integral [A <sup>2</sup> s]
823.605	63 mA	125 V	300 A	2.230	0,0002
823.608	125 mA	125 V	300 A	1.500	0,0010
823.611	250 mA	125 V	300 A	1.000	0,0070
823.650 <sup>1)</sup>	315 mA	125 V	300 A	1.000	0,0065
823.612 <sup>2)</sup>	375 mA	125 V	300 A	1.000	0,0060
823.613 <sup>1)</sup>	400 mA	125 V	300 A	1.000	0,0110
823.614	500 mA	125 V	300 A	1.000	0,0180
823.615 <sup>1)</sup>	630 mA	125 V	300 A	500	0,0230
823.616 <sup>2)</sup>	750 mA	125 V	300 A	275	0,0400
823.655 <sup>1)</sup>	800 mA	125 V	300 A	275	0,0420
823.617	1 A	125 V	300 A	275	0,0940
823.618 <sup>1)</sup>	1,25 A	125 V	300 A	275	0,1380
823.619 <sup>2)</sup>	1,5 A	125 V	300 A	275	0,3300
823.659 <sup>1)</sup>	1,6 A	125 V	300 A	275	0,4330
823.620	2 A	125 V	300 A	250	0,4100
823.621	2,5 A	125 V	300 A	250	0,8200
823.622 <sup>2)</sup>	3 A	125 V	300 A	250	1,5000
823.664 <sup>1)</sup>	3,15 A	125 V	300 A	250	1,2900
823.665 <sup>2)</sup>	3,5 A	125 V	300 A	250	1,800
823.623	4 A	125 V	300 A	225	3,2000
823.624	5 A	125 V	300 A	225	4,1000
823.626 <sup>2)</sup>	7 A	125 V	300 A	150	11,000
823.627 <sup>1)2)</sup>	10 A	125 V	50 A	125	30,000
823.628 <sup>1)2)</sup>	12 A	32 V	50 A	100	auf Anfrage / on request
823.629 <sup>1)2)</sup>	15 A	32 V	50 A	100	on request



Schmelzeit-Grenzwert / Pre-arcing time limits

Bemessungsstrom Rated current	1 I <sub>rat</sub> min.	2 I <sub>rat</sub> max.	2,75 I <sub>rat</sub> max.	4 I <sub>rat</sub> max.	10 I <sub>rat</sub> max.
63 mA – 10 A 12 A - 15 A 63 mA – 10 A		5 s 10 s	300 ms	30 ms	4 ms

1) kein UL/cUL - no UL/cUL approval  
2) kein CCC – no CCC approval