



		Customer Part NO. (客户部品号):	
		Part Descripon(部品规格): 0.5-32-150-A 2/4 (0.035*0.3) L-KLS17-FFC-0.5-32P-L150A2/4	
Item	项目	Specification	规格值
NO. of conductors	导体芯数 N	32P	
Pitch	间距 P	0.5±0.05	
Total Pitch	全间距 PT	15.5±0.05	
Total Length	总长度 L	150±2	
Insulation Length	绝缘长度 IL	146±2	
Margin Width	边缘宽度 M	0.5±0.08	
Total Width	总宽度 W	16.5±0.08	
Strip Length	线口长度 S1	2±0.5	
Strip Length	线口长度 S2	2±0.5	
Reinforeing tape length	补强板长度 B1	4±0.5	
Reinforeing tape length	补强板长度 B2	4±0.5	
Slanting	线口倾斜度 A	≤0.3	
Over lap	冲孔	/	
Terminal thickness	插入厚度 t1	0.3 ±0.05	
Thickness insulation	线身厚度 t	0.12 ±0.05	
Conductor thickness	导体厚度 Ct	0.035 ± 0.005	
Conductor width	导体宽度 Cw	0.3 ±0.05	
Supporting Tapc Color	补强板颜色	蓝色(Blue)	
PET (Supporing Tapc Color)	补强板规格	0.225mm	
PET (Insulation)	绝缘胶规格	0.043mm 印字	
PET (Insulation)	绝缘胶规格	0.043mm 白膜	
Rev	版本	A	

Storage condition(储存条件):Recommended(推荐)  
 Temp:15° C~25° C(温度15° C~25° C)Humidity:30~60RH%(湿度30~60RH%)

Drawing Not To Scale Hidden Lines Not Shown 图规不能以其线材比便来衡量，隐藏线不显示。	Discharge Date 发行日期	Review Date 修订日期	Drawing NO 图纸编号
 Unit(单位):mm	2006-05-01	2021-04-08	
	Drawing by 制图	Checked by 核对	Approved by 确认
	叶德远	刘凯	沈云霄