

# SOLDERING & DESOLDERING



## ▶ SS-969E / SS-969B SMD Rework Station



**Brushless motor**  
**Microprocessor-controlled**  
**Auto-sleep and work mode**  
**UL certified wires**  
**Durable metal case**



**700W**  
**450°C**



- Microprocessor-controlled with closed circuit sensor design, provide high power and quick warm up times.
- Adjustable air flow, air volume and temperature to meet variety applications.
- Handle with sensor design provides real-time operating.
- Brushless motor design, quiet in operation, equipment noise less than 45dB.
- Auto cool-off process to prolong the life of heating element.
- Silicone Handpiece cord wire heat-resistant up to 200°C.
- AWG 20 (0.5mm<sup>2</sup>) UL Certified Wires.
- Metal case with painting makes more durable.

| Specification        |   |                              |
|----------------------|---|------------------------------|
| Model No             | SS-969E   | SS-969B                      |
| Power Consumption    | 700W  |                              |
| Temperature Range    | 100~450°C(212~842°F)  |                              |
| Heating Element      | Metal Heating Core  |                              |
| Equipment Noise      | <45dB   |                              |
| Temperature Display  | LED   |                              |
| Air Volume           | 120L / min (Max.)   |                              |
| Fuse type            | 250V / 8A   | 250V / 5A                    |
| Input Voltage        | AC110V~120V, 60Hz   | AC220V~240V, 50Hz            |
| Plug Type            | E   | B                            |
| Machine Size (mm)    | 170 x 170 x 140   |                              |
| Overall Package (mm) | 280 x 185 x 170   |                              |
| Weight               | 1.43 kgs  |                              |
| Accessories          |   |                              |
| Heat Air Gun         | 5SS-969NE-HG<br>AC(110~120V)  | 5SS-969NB-HG<br>AC(220~240V) |
|                      | (225 x 60 x 40mm / wire length 140cm)   |                              |
| Nozzle               | 9SS-969-A1 x 1pcs ( ID: Ø 4.3mm )<br>9SS-969-A2 x 1pcs ( ID: Ø 7.4mm )<br>9SS-969-A3 x 1pcs ( ID: Ø 9.4mm ) |                              |
| Individual packing   | Color box   |                              |



Standard nozzles x 3 pcs



SMD rework



High quality assembly



Additional ground contact