

## Data sheet

Commercial Art.No.: 90.240.1000.2

Cable assembly GST08i3BS 75P 10WS

GST08i3 connection cable female - male, length 1.0 m, 3 pole, coding Mains 250 V, 6 A, coding color white, cable color white, cross section 0.75 mm<sup>2</sup>, cable type H03VV-F



Commercial Art.No.	90.240.1000.2
EAN	4049088365317
Order Unit	1

Certificates / Approvals



## Technical data

### General

Rated current	6 A
Rated voltage	250 V
Mechanical coding	yes
Lockable	No
Color of coding/ contact carrier	white
Color of housing inclusive strain relief	white

### Model

Nominal cross section conductor	0.75 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H03VV-F
Cable color	white
Cable diameter min.	6 mm
Cable diameter max.	5.5 mm
Version of cable	female - male
Type of cord set	connecting cable
Version cable end 1	GST08i3 socket
Version cable end 2	GST08i3 plug

### Material

halogen free	No
Continuous temperature of cable	70 °C

Insulation components continuous temperature	70 °C
Fire load	0 kWh

#### Dimensions

Total length	1 m
--------------	-----

#### Classification

ECLASS 11	
ECLASS 8.1	27440604
ETIM 7.0	EC002587
ETIM 6.0	EC002587
ETIM 5.0	EC002587
ETIM 4.0	EC002587

#### Product compliance

ROHS conformity status	Compliant
REACH-SVHC conformity status	Compliant

#### Fits with

Commercial Art.No.:	Article-type description:	Description:
90.240.0503.2	Cable assembly GST08i3B- 75P 05WS	GST08i3 extension cable female - free end, length 0.5 m, 3 pole, coding Mains 250 V, 6 A, coding color white, cable color white, cross section 0.75 mm <sup>2</sup> , cable type H03VV-F
90.240.0504.2	Cable assembly GST08i3-S 75P 05WS	GST08i3 extension cable male - free end, length 0.5 m, 3 pole, coding Mains 250 V, 6 A, coding color white, cable color white, cross section 0.75 mm <sup>2</sup> , cable type H03VV-F