

## ST Series Soldering Station



### Features:

- Temperature locking.
- Beep alarm function available.
- MCU controlled temperature calibration.
- User-friendly menu enables system setting easier.
- Separate iron stand to save room and to make easier deposit.
- Buttons(1,2,3) for pre-setting or switching frequently used temperature.
- Low-voltage heater separated from power supply to keep soldering work safer.

### Specification:

Product pictures			
Item No	ST-80	ST-909	ST-100
Voltage	AC(100V/110V/120V    220V/230V/240) 50/60Hz		
Power	80W	90W	100W
Temperature range	150°C~480°C	200°C~500°C	150°C~480°C
Temperature Stability	±2°C(in still air,no load)	±2°C(in still air,no load)	±2°C(in still air,no load)
The handle type	SP-80	SP-990	SP-100
Soldering tip type	T900-B	T990-K	T800-0.25I
Heater	High performance four-core ceramic heater HS-3080	Integrated heater	Sliver alloy heater HS-3100
Package list	Main unit: 1unit Handle set : 1 PCS	Iron stand: 1 PCS AC cord: 1 PCS	Manual: 1 PCS Cleaning sponge: 1 PCS
Standard Packing	Inner box: 31.5x27x15.2(cm) N.W.: 2.09kg G.W.: 2.32kg Carton: 6PCS/Carton Size: 55.5x33x48(cm) N.W.: 14.4kg G.W.: 15.4kg	Inner box: 24.6x22.4x14.2(cm) N.W.: 2.2kg G.W.: 2.4kg Carton: 8PCS/Carton Size: 50.7x46.3x30.9(cm) N.W.: 19.2kg G.W.: 20.0kg	Inner box:31.5x27x15.2(cm) N.W.: 2.68kg G.W.: 2.95kg Carton: 6PCS/Carton Size: 55.5x33x48(cm) N.W.: 17.9kg G.W.: 19.0kg
Applicable	<ul style="list-style-type: none"> <li>● Institutes</li> <li>● Enterprises</li> <li>● Education and practice</li> <li>● Maintenance ● Hobby</li> </ul>		