

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY TYCO ELECTRONICS CORPORATION

ALL RIGHTS RESERVED.

LOC DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A5	RELEASE PER ECR-19-009634	15JUL2019	LZ	TD

19

B

E

E

B

NOTE:

- CONTINUOUS STRIP ON REELS
- MATING TAB ACCORDING TO UL310 AND IEC61210 NORM. (WIDTH\*THICKNESS IS 6.3\*0.8mm)
- WIRE SIZE IS #18-#14 AWG(1.0-2.5 sqmm)
- INSULATION RANGE IS  $\varnothing$ 3-4.3mm
- CUT-OFF TAB LENGTH 0.5mm MAX.
- PRELIMINARY NOT FOR PRODUCTION.
- APPLICATION FEED LENGTH 21.4mm.

2.6

0.8

0.40

7.6

0.4

7

8.8

4.4

2.5

0.5 Max.

0.5 Max.

3.8

(4)

SECTION E-E

5.5

(5.1)

SECTION B-B

Pre-Tin Plated	CuNiSi	2178300-3	6
Pre-Tin Plated	BRASS	2178300-2	6
Pre-NICKEL	Steel	2178300-1	
FINISH	MATERIAL	PART NO.	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	29NOV2012	 TE Connectivity	
DIMENSIONS:		CHK	29NOV2012		
mm		APVD	29NOV2012		
		PRODUCT SPEC	108-64027		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	SURESH T N	NAME	
0 PLC	±0.5	PRODUCT SPEC	114-64027	6.3 SRS F-SPRING	
1 PLC	±0.5	APPLICATION SPEC	114-64027	LIF RECEPTACLE	
2 PLC	±0.1	WEIGHT	-	SIZE	A3
3 PLC	±	Customer Drawing		CAGE CODE	00779
4 PLC	±			DRAWING NO	©=2178300
ANGLES	±1°			RESTRICTED TO	-
FINISH	SEE TABLE			SCALE	4:1
				SHEET	1 OF 1
				REV	A5

1470-19 (3/11)