

Brass Breathable Gland



螺牙规格 Thread	规格 Sizes	适用电缆 Cable	螺纹外径 Thread O.D C1	螺纹长度 Thread Length C2	透气量 Air permeability	压力范围 Pressure range
M10x1.5	M10-BR	3-6.5	10	6.5	400ML/min	P=7kpa
M12x1.5	M12S-BR	3-6.5	12	6.5	650ML/min	P=7kpa
	M12L-BR	4-8	12	7	800ML/min	P=7kpa
M14x1.5	M14-BR	4-8	14	7	800ML/min	P=7kpa
M16x1.5	M16S-BR	4-8	16	8	1000ML/min	P=7kpa
	M16L-BR	5-10	16	8	1200ML/min	P=7kpa
PG7	PG7-BR	3-6.5	12.5	6.5	650ML/min	P=7kpa
PG9	PG9-BR	4-8	15.2	7	800ML/min	P=7kpa
PG11	PG11-BR	5-10	18.6	8	1200MI/min	P=7kpa

Application Area: Lighting Industry, Automation Technology, Wind-solar Energy, Industrial Equipment

Material: Metal parts: Brass with/without nickel plated/AISI303/316L Stainless Steel
 Plastic parts: PA6
 Sealing: NBR
 O-ring: NBR
 Breathable film: EPTFE

Protection Rate: IP68

Temperature Range: -40°C - 105°C

Nylon Breathable Gland



螺牙规格 Thread	规格 Sizes	适用电缆 Cable	螺纹外径 Thread O.D C1	螺纹长度 Thread Length C2	透气量 Air permeability	压力范围 Pressure range
M12x1.5	M12S-NBR	3- 6.5	12	8.5	800ML/min	P=7kpa
	M12L-NBR	4- 8	4- 8	8.5	800ML/min	P=7kpa
M16x1.5	M16-08	4-8	16	10	800ML/min	P=7kpa
	M16-10	6-10	16	10	800ML/min	P=7kpa
M20x1.5	M20S-NBR	5-9	20	15	800ML/min	P=7kpa
	M20L-NBR	6-12.5	20	15	800ML/min	P=7kpa
PG9	PG11S-NBR	4-8	16	10	800ML/min	P=7kpa
	PG11L-NBR	6-10	16	10	800ML/min	P=7kpa
PG13.5	PG13.5-NBR	7-12.5	20.4	10	800ML/min	P=7kpa

Application Area: Lighting Industry, Automation Technology, Wind-solar Energy, Industrial Equipment

Material: Nylon PA6

Flat Washer: NBR

Protection Rate: IP66/IP67

Temperature Range: -40°C - 100°C ,short time : -20°C - 80°C