





• **SFM-1440**



**FEATURES:**

- This item is designed for surface mounting applications
- The pin is plated with gold, which can meet the request of re-flow soldering process at 260°C for 30 seconds.
- Small size


**DIMENSIONS: (Unit: mm)**



SFM-TERMINAL VERSION

RECOMMENDED SMD FOOT PATTERN


**CHARACTERISTICS:**



ELECTRICAL SPECIFICATIONS :	
<b>Model No.</b>	<b>SFM-1440</b>
Min. Sound Pressure Level (dB)	75 /4.0kHz /5Vp-p Square Wave /10cm
Capacitance at 1000Hz (nF)	10 ± 30%
Allowable Input Voltage (Vp-p)	20
Max. Consumption (mA)	2 /4.0kHz /5Vp-p Square Wave
Resonant Frequency (kHz)	4.0 ± 0.3
Operating Temperature (°C)	-20 ~ +85
Case Material/Colour	PPS/Black
Weight (g)	1.1
PACKING INFORMATION:	
Packing	10000 pcs per export carton
Carton Size	50.5 X 29 X 16 cm
G. Weight	16.4 kgs
N. Weight	11 kgs
N. Weight	11 kgs

**TAPE TYPE INFORMATION:**


The design for such tape packing was executed under standard IEC -286-3  
The material of the tape is polystyrene in black color. detailed dimensions are as below :



**PACKING INFORMATION:**

**DIMENSIONS OF THE ROLLING PLATE:**

The material of the rolling plate is in paper;  
The dimensions of the rolling plate are as below:



**PACKING DIMENSIONS AND QUANTITY:**

- The rolling plate is put into a 340X335X35mm inner packing box and is packed with 650 pcs of the transducer per plate.
- The dimension of the outer carton is 400X350X350mm containing 10 inner boxes with a total quantity of 6,500 pcs of the transducer.
- The total gross weight per carton is 12.7Kgs,while net weight is 7.2Kgs.