


Screw clamping terminal block-  
UKJ-4/2-2- 011017






Screw clamping terminal block , rated voltage:600V , Max. operating current:32A, connection method : screw connection , number of connections : 4 , crimping range : 0.2mm<sup>2</sup> -4mm<sup>2</sup> , thickness:6.2mm , height:61mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	80
NW per piece(g)	1.18
Layers	2
Number of connections	4
Rated cross section(mm <sup>2</sup> )	4
Color	grey
Insulation material	PA
Flame retardant grade ( UL94 )	V0
Rated voltage(V)	600
Rated current(A)	32
Temperature of insulation material	-40 ~ +125
Wire feed	Left and right side of the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
	
Certification logo	<b>IECEX</b>
Certification logo	<b>cRU<sup>®</sup> US</b>
Certification logo	
Certification logo	<b>RoHS</b>

## Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3
Stripping length(mm)	8
Tightening torque	0.6-0.8
Solid conductors(mm <sup>2</sup> )	0.2-4
Stranded conductors(mm <sup>2</sup> )	0.2-4
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

## Dimension

Parameter	Data
Width(mm)	56.5

Parameter	Data
Thickness(mm)	6.2
Height(mm)	61