




REVISION RECORD			
REV	ECN	DESCRIPTION	DRFT DATE
Δ	new	ding	2022.11.09



Connection method:
 1.For solid wire, peeling wire in right length, fix in by rated torque force.
 2.For stranded wire,connect directly after peeling in right length,or furrled on wire and fix in by rated torque force.
 (Attention:torque force should be equable, no explosive power.)

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited.
 未经允许禁止传输、复制、编辑该文档，以及利用其内容进行交流

- NOTES:
 UL/CUL Standard
 1.Conductor cross section : 26~8AWG
 2.Rated torque : M4 , 10.53~13.3Lb.in
 M3 , 5.32~7.02Lb.in
 3.Rated Voltage/Current :
- | Use group | B | C | D |
|------------------|-----|-----|---|
| Rated voltage(V) | 300 | 300 | |
| Rated current(A) | 50 | 50 | |

Surge voltage category	III
Pollution degree	3
Rated surge voltage(KV)	6
Rated voltage(V)	400
Rated current(A)	41

Material:
 Insulator PA66 UL94 V-0
 Conductor Copper alloy Sn plated

- IEC Standard
 1.Conductor cross section :
- | Wire range(Solid/Stranded) | 0.5-6mm ² |
|---|-----------------------|
| Solid | 0.5-10mm ² |
| Stranded | 0.5-6mm ² |
| Stranded with ferrules without plastic sleeve | 0.5-6mm ² |
| Stranded with ferrules with plastic sleeve | 0.5-4mm ² |
- 2.Rated torque : M4 , 1.2~1.5N•m
 M3 , 0.6~0.8N•m
 3.Rated Voltage/Current :

- General information:
 1.Dimension shall be interpreted per ASME Y14.5-2009
 2.Stripping length : 13-14mm
 3.Operating temperature: -40°C~+105°C
 4.RoHS Compliance
 5.Undimensioned Tolerances:
- | Pitch Range in mm | Nominal Dimension | Range |
|-------------------|-------------------|------------|
| Over 6 | Over 30 | Over 60 |
| TO 10 | TO 30 | TO 60 |
| 6 TO 10 | 24 TO 30 | 60 TO 100 |
| | | 100 TO 150 |
| ±0.15 | ±0.20 | ±0.30 |
| | | ±0.50 |
| | | ±0.70 |
| | | ±1.00 |
| | | ±1.30 |

订货号	30691X	名称	URTK/S 封装螺钉接线端子	公差	表面
Item	Signature	图号	PRM...	Tolerances Table	Surface
Design	CJS	材料	Notes	版本号	VDI21
Check	CW	Material		Revision Number	Weight
Process	-	Material		M1	Scale
标准化	-	物料号			1:1
批准	-	Item No.			
批准	LWL				
日期	05/09/19"				

订货号	颜色	Part Number	颜色	306916	黑色/Black
306911	灰色/Gray	306911	灰色/Gray	306917	黄色/Yellow
306912	蓝色/Blue	306912	蓝色/Blue	306918	白灰色/Light gray
306914	橙色/Orange	306914	橙色/Orange		
306915	红色/Red	306915	红色/Red		

原图号
 Old Draw. No.
 底图总号
 Assembly No.

普通零件登记
 Common Part
 借图号
 Borrowing No.