

PRODUCT DETAILS

Model	Voltage (V)	Current (A)	Power (W)	Air Volum (CFM)	Speed (Rpm)	Noise Level (db)
RQD2510HS	5	0.25	1.25	2.11	12000	29
RQD2510MS	5	0.16	0.80	1.60	1000	23
RQD2510LS	5	0.14	0.70	1.22	7000	21
RQD2510HS	12	0.12	1.44	2.11	12000	29
RQD2510MS	12	0.09	1.08	1.60	10000	23
RQD2510LS	12	0.05	0.60	1.22	7000	21

General description of the:

Each of the fans has DC brushless motor for driving, a tubular frame and plastic impeller. they have some superior features such as large air volume, low noise ,low EMI, low power consumption, high efficiency and long life etc. they are specially used in computer system. office automation products, and automatic applications on the ground for air cooling and venting where there is a DC power supply.

Application cond itons:

Temperature Range(°C):-20°C+60°C Ball Bearing(B) -20°C+40°C Sleeve Bearing(S);

Humidity permissible(%):≤90%(25°C);

Atmospheric Pressure 55kpa;

Vibration Permissible: Frequency 10Hz, Double Amplitude 1.5mm;

Impact Permissible: (peak acceleration)40m/ S²

ILLustration Of The Code:

