

Push-in terminal blocks-
UJ6-2.5SK-421490



Terminal block, Rated voltage: 500V, Rated current: 20A, connection methods: circlip connection, number of connection: 2, crimping range: 0.2mm² -4mm² , AWG : 24-12 , thickness 5.2mm, height 59.4mm, color: grey, mounting rail: TH35-7.5、 TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	60
NW per piece(g)	7.2
Layers	1
Number of connections	2
Rated cross section(mm ²)	2.5
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	500
Rated current(A)	20
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	13
Solid conductors(mm ²)	0.2-4
Solid conductors AWG	24-12
Stranded conductors(mm ²)	0.2-2.5
Stranded conductors AWG	24-14
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	59.4
Thickness(mm)	5.2
Height(mm)	35.2