

Data sheet

Commercial Art.No.: 93.422.0653.1

Device connector BST14i2L S1 GN01

Device connectors, PCB mount, BST14i2, 2 pole, horizontal, male, 50V/3A, color of coding: green, color of housing: black



Commercial Art.No.	93.422.0653.1
EAN	4015573600270
Order Unit	1

Certificates / Approvals



Technical data

General

Rated current	3 A
Rated voltage	50 V
Pollution degree	2
Mechanical coding	yes
Rated impulse voltage	0.8 kV
Lockable	self-locking (unlocking by hand)
Color of coding/ contact carrier	green
Marking of poles	1+, 2-
Color of separate adapter (if present)	black

Connection Data

Terminations per pole	1
-----------------------	---

Model

Model	male
Connection type	Soldering connection
Angle of plug	Square
Degree of protection (IP)	IP20
built-in component	Soldering connection

Material

Housing material	Polyamide
halogen free	yes

Contact material	CuBe
Fire load	0.017 kWh
Insulation components continuous temperature	100 °C
Surface finish	Gilt

Dimensions

Length	26 mm
Width	13 mm
Height	11.75 mm

Classification



ECLASS 11	
ECLASS 8.1	27440602
ETIM 7.0	EC002566
ETIM 6.0	EC002566
ETIM 5.0	EC002566
ETIM 4.0	EC002566

Product compliance

ROHS conformity status	Compliant
REACH-SVHC conformity status	Compliant

Fits with

Commercial Art.No.:	Article-type description:	Description:
93.421.0553.1	Connector BST14I2F B1 ZR1 S MGN01	Connector BST14I2, 2 pole, female, spring clamp connection, 50V/3A, color of coding: green, color of housing: black



STECKERTEIL
 93.422.0653.0 10W
 24.04.2008 Weisensel F.
 M 2:1