

Alkaline LR6 AM-3 AA

Technical Data:

Nominal Voltage:1.5V

Average Weight:21.5±0.2g

Diameter:13.7-14.5mm

Height:49.5-50.5mm

Discharge Performance(20±2℃ , RH:35%-75%)

Load	1500mW/2s 650mW/28s	3.9Ω	3.9Ω	100mA	250mA	50mA
Discharge Mode	10T/h	1h/d	4min/h,8h/d	1h/d	1h/d	1h/8h,24h/d
End-Voltage	1.05V	0.8V	0.9V	0.9V	0.9V	1.0V
Initial Phase	60 time	6.5h	380 min	21.0h	7.0h	43.0 h
After 12months storage	55 time	6.2h	360 min	20.0h	6.5h	41.0 h

Packing Specification

Type	Jacket	Pack	Inner Box(pcs)	CTN (pcs)	Meas.(cm)	G.W (kgs)
LR6 AM-3 AA	Aluminum	4pcs/shrink	40	800	30.5x30.5x11.8	18.5
LR6 AM-3 AA	Aluminum	2pcs/card	24	480	51.0x28.0x18.7	12.0
LR6 AM-3 AA	Aluminum	4pcs/card	48	960	51.0x28.0x18.7	24.0