


Screw clamping terminal block- UKJ-50-011013







Screw clamping terminal block , rated voltage:1000V , Max. operating current:150A, connection method : screw connection , number of connections : 2 , crimping range : 16mm² -50mm² , thickness:20mm , height:76mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	10
NW per piece(g)	1.19
Layers	1
Number of connections	2
Rated cross section(mm ²)	50
Color	grey
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	1000
Rated current(A)	150
Temperature of insulation material	-40 ~ +125
Wire feed	Left and right side of the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
	
Certification logo	
Certification logo	CCS
Certification logo	IECE_x
Certification logo	cRU[®] US
Certification logo	
Certification logo	RoHS

Technical data

Parameter	Data
Connection Method	
Screw thread	
Stripping length(mm)	
Tightening torque	
Solid conductors(mm ²)	
Stranded conductors(mm ²)	

Parameter	Data
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	71
Thickness(mm)	20
Height(mm)	76