



		尺寸公差(mm)				
		0	>30	>60	>100	0.05/1.0
Rated current	10A	~	~	~	~	±T [*]
Rated voltage	300V	30	60	100	150	
Coil/Contact dielectric voltage	4000V/S					
Dielectric voltage between contact	2500V/S					
Screw torque	1.0Nm					
External connection wire	20-14/0.5-2.5W					
Ambient temperature	G/mm ²					
Key controlled symbol	-45~+85℃					*
Conform to RoHS						

Printing for laser marking/printing content is clear ,no broken line/rect
Seal literal reference according to the foot position in the drawing

REV	ECN	DESCRIPTION	DRAFT	DATE

1	DSRT08A-3-00A(H)-N	300190000039	1		
MATERIAL: /		SURFACE: /			
MAT. NO.: 300200000058					
STATUS: /					
APPD: /		Description:			
CHKD: /		NINGBO DEGSON ELECTRICAL CO., LTD 宁波高松电子有限公司			
DRAFT: /		DRAWING NO.: 300000366		REV TO-1	
SIZE: A4		TYPE: PRODUCT DRAWING		SCALE: 1:1 SHEET 1/1	

DSRT08A-3-00A(H)

NINGBO DEGSON ELECTRICAL CO., LTD
宁波高松电子有限公司

1

2

3

4

5

6

D

C

B

A