

# CENTER 510

## Carbon Monoxide(CO) Meter



### **FEATURES:**

- Large LCD dual displays for CO and TEMP measurement.
- Backlight for easy screen viewing under dim lighting conditions.
- Adjustable alarm limits.
- CO level beeper can be silenced if desired.
- Automatic Zero point adjustment.
- Max Hold function.
- Data Hold function.
- Auto Power Off.
- Easy to replace battery.
- Replaceable co sensor extends tool life.

CE

**CENTER**®

# CENTER 510 Carbon Monoxide (CO) METER

## FEATURES

- Large LCD dual displays for CO and TEMP measurement.
- Backlight for easy screen viewing under dim lighting conditions.
- Adjustable alarm limits.
- CO level beeper can be silenced if desired.
- Automatic Zero point adjustment.
- MAX Hold function.
- Data Hold function.
- Auto Power Off.
- Easy to replace battery.
- Replaceable CO sensor extends tool life.

## SPECIFICATIONS

**Meas. Range:** CO: 0 to 1000 ppm; Temp: -10 to 60°C, 14 to 140°F

**Resolution:** 1 ppm, 0.1°C, 0.1°F

**Accuracy:** 5% or 10 ppm, ±0.8°C, ±1.5°F

**Sensor Type:** Stabilized electrochemical CO specific sensor;  
Thermistor temp sensor.

**Alarm limits:** Adjustable.

**Sensor life:** 3 years (typical).

**Power:** 4 AA size battery.

**Battery life:** 200 hours (typical)

**Dimensions:** 190 x 65 x 43 mm

**Weight:** 245 g



LED Back Light



## APPLICATIONS

- Ambient air safety checks on residential appliance.
- HVAC service on furnaces and hot water heaters.
- Home inspections.
- Industrial environments where the accumulation of CO is possible.



**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**



\*The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by:

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,  
New Taipei City 238, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http: //www.centertek.com