

## Data sheet

Commercial Art.No.: 91.232.2009.2

Cable assembly GST15i3KSBA 15 W 20WS

GST15i3 adaptor cable female GST15 - male GST18, length 2.0 m, 3 pole, coding mains 250 V, 16 A, coding color white, strain relief color white, cable color white, cross section 1.5 mm<sup>2</sup>, cable type H05VV-F, fire class: Eca



Commercial Art.No.	91.232.2009.2
EAN	4015573837881
Order Unit	1

## Technical data

### General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	white
Marking of poles	L, N, PE
Color of housing inclusive strain relief	white

### Model

Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable color	white
Cable diameter max.	8.3 mm
Version of cable	GST18i3 male – GST15i3 female
Type of cord set	adapter cable
Version cable end 1	GST15i3 socket
Version cable end 2	GST18i3 plug

### Material

Surface finish	Silver-plated
halogen free	No
Continuous temperature of cable	70 °C

Insulation components continuous temperature	100 °C
Fire load	0.901 kWh
Fire class	Eca

**Dimensions**


Total length	2 m
--------------	-----

**Classification**

ECLASS 11	
ECLASS 8.1	27440604
ETIM 7.0	EC002587
ETIM 6.0	EC002587
ETIM 5.0	EC002587
ETIM 4.0	EC002587

**Product compliance**

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1



für folgende Tabellen-Zchnng.:  
91.232.0209.1 GST15I3KSBA 15...

KONFEKT. LEITUNG  
91.232.0209.1 10W  
13.02.2008 Lunz S.  
M 1:2